

## Constant Support

## Check List for Requesting a Quote or Ordering

Page \_\_\_ of \_\_\_



Anvil International  
Precision Park  
160 Frenchtown Rd.  
North Kingstown, RI 02852

For technical information regarding  
Constant Supports Call or Fax:  
Fax Number: (401) 886-3056  
Phone Number: (401) 886-3025

**Finish:** Standard Primer: \_\_\_\_\_ Galvanized: \_\_\_\_\_ Special Coating: \_\_\_\_\_

**Quantity:** \_\_\_\_\_

**Figure No.:** Options are:  80-V,  81-H  
or:  C-80-V,  C-81-H

**Size:** Options are: #1 through #110 (*Size #1 through #9 available in 81-H only*) \_\_\_\_\_

**Type:** Options are: A through G\* (*Type F Upthrust available in 81-H only, Type G available in 80-V only*) \_\_\_\_\_

**Actual Travel (AT):** \_\_\_\_\_ (inches)

**Total Travel (TT)\*\*:** \_\_\_\_\_ (inches)

**Direction of Travel:** \_\_\_\_\_ + (up) or - (down)

**Load:** \_\_\_\_\_ (lbs)

**"J" Dimension (rod diameter):** \_\_\_\_\_ (inches) (Not required for Type F)

**Mark Number:** \_\_\_\_\_ (If required)

**Travel Stops:** Are always Included

**Lifting Lugs:** Yes: \_\_\_\_\_ No: \_\_\_\_\_  
*Available on sizes 10 and larger.*

### Notes:

\* *Type G Constants must also include the C-to-C dimension & the load per spring.*

\*\* *Total Travel = Actual travel + 1" or 20% whichever is greater rounded up to the next one half inch increment.*

